


















Improvised Explosive Device (IED) Safe Standoff Distance Cheat Sheet

Threat Description		Explosives Mass ¹ (TNT equivalent)	Building Evacuation Distance ²	Outdoor Evacuation Distance ³
High Explosives (TNT Equivalent)		Pipe Bomb 5 lbs 2.3 kg	70 ft 21 m	850 ft 259 m
		Suicide Belt 10 lbs 4.5 kg	90 ft 27 m	1,080 ft 330 m
		Suicide Vest 20 lbs 9 kg	110 ft 34 m	1,360 ft 415 m
		Briefcase/Suitcase Bomb 50 lbs 23 kg	150 ft 46 m	1,850 ft 564 m
		Compact Sedan 500 lbs 227 kg	320 ft 98 m	1,500 ft 457 m
		Sedan 1,000 lbs 454 kg	400 ft 122 m	1,750 ft 534 m
		Passenger/Cargo Van 4,000 lbs 1,814 kg	640 ft 195 m	2,750 ft 838 m
		Small Moving Van/ Delivery Truck 10,000 lbs 4,536 kg	860 ft 263 m	3,750 ft 1,143 m
		Moving Van/Water Truck 30,000 lbs 13,608 kg	1,240 ft 375 m	6,500 ft 1,982 m
		Semitrailer 60,000 lbs 27,216 kg	1,570 ft 475 m	7,000 ft 2,134 m
Threat Description		LPG Mass/Volume ¹	Fireball Diameter ⁴	Safe Distance ⁵
Liquefied Petroleum Gas (LPG - Butane or Propane)		Small LPG Tank 20 lbs/5 gal 9 kg/19 l	40 ft 12 m	160 ft 48 m
		Large LPG Tank 100 lbs/25 gal 45 kg/95 l	69 ft 21 m	276 ft 84 m
		Commercial/Residential LPG Tank 2,000 lbs/500 gal 907 kg/1,893 l	184 ft 56 m	736 ft 224 m
		Small LPG Truck 8,000 lbs/2,000 gal 3,630 kg/7,570 l	292 ft 89 m	1,168 ft 356 m
		Semitanker LPG 40,000 lbs/10,000 gal 18,144 kg/37,850 l	499 ft 152 m	1,996 ft 608 m

¹ Based on the maximum amount of material that could reasonably fit into a container or vehicle. Variations possible.

² Governed by the ability of an unreinforced building to withstand severe damage or collapse.

³ Governed by the greater of fragment throw distance or glass breakage/falling glass hazard distance. These distances can be reduced for personnel wearing ballistic protection. Note that the pipe bomb, suicide belt/vest, and briefcase/suitcase bomb are assumed to have a fragmentation characteristic that requires greater standoff distances than an equal amount of explosives in a vehicle.

⁴ Assuming efficient mixing of the flammable gas with ambient air.

⁵ Determined by U.S. firefighting practices wherein safe distances are approximately 4 times the flame height. Note that an LPG tank filled with high explosives would require a significantly greater standoff distance than if it were filled with LPG.